


205W-12043-P-ABC

water-cooled motor / generator with 82 kW continuous power

This datasheet refers to art.no.: see page 2



KEY FEATURES

- permanent magnet synchronous machine
- water-cooled
- high peak power for motor applications
- convincing cost-benefit ratio
- recommended voltage range from 350 V to 850 V
- delivery with controller possible

Section	Page
Operating Range	3
Additional Data	4
Available Type Variants	5
Technical Drawings	6
Performance Plots	7

Note:

On September 1st, 2024, we transferred our ERP systems to SAP. Due to this change, we are altering our **current part numbers**. To see how our article numbers and motor naming scheme has changed, please consider the conversion table below:

Article Number Conversion				
Part. No.	Old Part. No.	Flange	Shaft	Position Sensor
4872387	205W_12043_CDF_P	C1	D1	F
4872391	205W_12043_CGF_P	C1	G1	F
4872393	205W_12043_SSF_P	S1	S1	F

To be noted:

The information in this technical data sheet is based on our current knowledge and experience. Due to the wide range of possible influences during application, they do not exempt the processor and user from carrying out their own tests and trials. Although the suitability for a specific application can be estimated from our information, a legally binding assurance is by no means possible. Depending on the individual case, we recommend consultation with us. Any industrial property rights and applicable laws must be observed by the recipient of our products on his own responsibility.

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.


Characteristic Operating Points¹⁾

		S1	S2	S2	
Feasible operation time	t_{on}	continuous	30 min	30 sec	
Torque ²⁾	T	117	117	285	Nm
Power ²⁾	P	82	82	156	kW
Speed	n	6750	6750	5250	rpm
Phase RMS-current (AC) ³⁾	I_{rms}	99	99	290	A
Battery current (DC) ³⁾	I_{DC}	108	108	219	A
Battery voltage (DC)	U_{DC}	800	800	800	V
Electric frequency	f_{el}	450	450	350	Hz
Efficiency	η_{tot}	97	97	92	%
Power factor	$\cos(\varphi)$	0.85	0.85	0.66	
Cooling	specified in chapter „Additional Data“				


Maximum Operating Range

Torque ^{2) 4)}	T_{max}	285 @ 5250 rpm			Nm
Power ^{2) 4)}	P_{max}	156 @ 5250 rpm			kW
Speed ⁵⁾	n_{max}	9000			rpm
Phase RMS-current (AC) ^{3) 4)}	$I_{rms,max}$	290			A
Battery current (DC) ^{3) 4)}	$I_{DC,max}$	219			A
Battery voltage (DC) ⁶⁾	U_{max}	850			V
Electric frequency	f_{el}	600			Hz

S1



S2



- 1) Defined Range only valid for a power factor of 1 at DC input
- 2) Torque / Power rating is dependent on rotor temperature
- 3) The cables must not exceed a temperature of 140 °C at any time. Temperature and service life depend on the installation condition.
- 4) Peak rating for max. 30 sec on time
- 5) Higher speeds available upon request. A detailed discussion of the functional safety concept of the vehicle is required.

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Electrical Data					
Number of phases		3			
Number of pole pairs		4			
Maximum stationary short circuit current ¹⁾		139 A (RMS) @ 20 °C, ≥ 700 rpm			
Maximal efficiency		97			%
T/I constant (I<I _{nom})		1.179			Nm/A _{rms}
U/n constant (AC) at temperature 20 °C		rms:	78.05	peak:	127.22 V/(1000rpm)
Ke constant (AC) at temperature 20 °C		rms:	0.75	peak:	1.21 V/(rad*s ⁻¹)
Additional Data					
Rotor moment of inertia		0.0208 (S1S1), 0.0212 (C1D1), 0.0211 (C1G1)			kg*m ²
Allowed range of ambient temperature ²⁾		-20 ... +85			°C
Maximal motor temperature		140			°C
Temperature monitoring		KTY-84-130			
Cooling	Advised medium (OAT Coolants)	water/glycol - 50/50 <ul style="list-style-type: none">▪ TL 774-D/F▪ VIN 878389▪ MAN 324 SNF▪ MTL 5048			
	Flow rate	6			l/min
	Inlet temperature	45			°C
	Pressure drop	0.138			bar
	Maximum pressure	2			bar
	Cooling channel volume	0.89			l
Connectors					
Power terminals		Prepared for M8 cable lugs; 3x M25 cable glands (not included)			
Signal connectors		1x Hummel 10 Pin Connector, M16			
Cooling connectors		inner Ø 12 mm, outer Ø 19 mm			
Certifications					
Type approval		CE, EN 60034			
Salt mist		ISO 9227			
Protection grade		IP6K9K ³⁾			
Vibrations		Prepared for ISO 16750-3			
Customs tariff number		8501 5381			

1) Simulated









2) Linear derating from 70 °C to 0 A at 85 °C

3) Please note that the IP6K9K rating is only valid if the machine is installed with suitable cable glands and an appropriate sealed interface at the drive side of the motor (flange and/or shaft). Please contact ENGIRO for further questions

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Shaft and Flange Combinations for 205W-12043-ABC		Flange (A)	
		S1 (Standard with 4xM10x35 threaded stud)	C1 (Hydraulic Pump ANSI 101-2 / SAE B - Ø101,6 mm centering hole)
Shaft (B)	S1 (Cylindrical shaft with keyway Ø 28mm)	● (≈ 46 kg)	
	D1 (Hollow shaft with internal splines ANSI B 92.1 / 15T 16/32DP30°)		● (≈ 48 kg)
	G1 (Hollow shaft with internal splines ANSI B 92.1 / 13T)		● (≈ 49 kg)
Position Sensor (C)		F: resolver gain 0.29 R: resolver gain 0.5 (Please note: The R resolver is a phase-out version with a 0.5 gain, which is replaced by the F resolver with a 0.29 gain)	


Other individual combinations are also possible on request.

**Flange C1
Shaft D1**

**Flange C1
Shaft G1**

**Flange S1
Shaft S1**



Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

800 V

Simulated Efficiency of Motor Application

(electric machine only; $U_{nom} = 800\text{ V}$)**800 V**

Simulated Characteristic Motor Parameters

 solid lines: S1 continuous; dashed lines: S2 (30 sec) maximum
 (cooling as specified in chapter "Additional Data")


Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.