



260W-25011-ABC-P

water-cooled motor / generator with 265 kW continuous power



Part no.: 4843401
Article Name: EN1_800V_900A_W

KEY FEATURES

- permanent magnet synchronous machine
- water-cooled
- high peak power for motor applications
- convincing cost-benefit ratio
- recommended voltage range from 350 V to 850 V
- delivery with controller possible

Section	Page
Operating Range	3
Additional Data	5
Available Type Variants / Technical Drawings	6
Performance Plots	7
Additional Characteristics	8

Note:

On September 1st, 2024, we transferred our ERP systems to SAP. Due to this change, we are altering our current part numbers.

From now on, configurations regarding the rear interface of the motor (e.g., accessible rear shaft end, closed, ...) will be specified in a separate part of the motor naming. Therefore, all 260W **D1-flanges** will be renamed to **S1-flanges** with the according B-side specification.

To see how our article numbers and motor naming scheme has changed, please consider the conversion table below:

Article number conversion					
Part.no.	Old part.no.	Flange	Shaft	Position sensor	B-side interface
4843046	260W_25011_SFR_P	S1	F1	R	...S11

To be noted:

The information in this technical data sheet is based on our current knowledge and experience. Due to the wide range of possible influences during application, they do not exempt the processor and user from carrying out their own tests and trials. Although the suitability for a specific application can be estimated from our information, a legally binding assurance is by no means possible. Depending on the individual case, we recommend consultation with us. Any industrial property rights and applicable laws must be observed by the recipient of our products on his own responsibility.

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.


Characteristic Operating Points ¹⁾

		S1	S2	S2	
Feasible operation time	t_{on}	continuous	30 min	30 sec	
Torque	T	634	634	1297	Nm
Power	P	265	265	475	kW
Speed	n	4000	4000	3500	rpm
Phase rms-current (AC)	I_{rms}	342	342	894	A
Battery current (DC)	I_{nom}	371	371	689	A
Battery voltage (DC)	U_{nom}	750	750	750V	V
Electric frequency	f_{el}	333	333	270	Hz
Efficiency	η_{tot}	95	95	87	%
Power factor	$\cos(\varphi)$	0.9	0.9	0.61	
Cooling		specified on page 5			


Maximum Operating Range

Torque	T_{max}	1297 @ 3500 rpm ²⁾			Nm
Power	P_{max}	475 @ 3500 rpm			kW
Speed	n_{max}	6000			rpm
Phase rms-current (AC)	$I_{rms,max}$	894 ^{3) 4)}			A
Battery current (DC)	I_{max}	723 ^{3) 4)}			A
Battery voltage (DC)	U_{max}	850			V
Electric frequency	f_{el}	500			Hz

S1




S2



- 1) Defined Range only valid for a power factor of 1 at DC input
- 2) Torque rating is dependent on rotor temperature
- 3) The cables must not exceed a temperature of 140 °C at any time. Temperature and service life depend on the installation condition.
- 4) Peak rating for max. 60 seconds on time

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

S9 Operating Points Maximum Feasible Power in % of S1						
U _{nom} = 750 V		Prior operating point in % of S1				
		0 %	25 %	50 %	75 %	100 %
On time t _{peak}	30 s	170%	160%	150%	130%	100%
	180 s	130%	120%	120%	110%	100%
	420 s	105%	100%	100%	100%	100%



Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Electrical Data					
Number of phases		3			
Number of pole pairs		5			
Maximal efficiency		95			%
T/I constant (I<Inom)		1.85			Nm/A _{rms}
U/n constant (AC) at temperature 30°C		rms:	117.7	peak:	175.7 V/(1000rpm)
Ke constant (AC) at temperature 30°C		rms:	0.281	peak:	0.419 V/(rad*s ⁻¹)
Additional Data					
Rotor moment of inertia		0.1677			kg*m ²
Allowed range of ambient temperature		-20 ... +85			°C
Maximal motor temperature		operating point dependent ¹⁾			
Temperature monitoring		1 x KTY84-130			
Cooling	Advised medium (OAT Coolants)	water/glycol - 50/50 <ul style="list-style-type: none">▪ TL 774-D/F▪ VIN 878389▪ MAN 324 SNF▪ MTL 5048			
	Flow rate	20			l/min
	Inlet temperature	45			°C
	Pressure drop	0.5			bar
	Maximum inlet pressure	2			bar
	Cooling channel volume	2.17			l
Connectors					
Power terminals		3 x M32 cable gland			
Signal connectors		M16, Hummel 10 Pin connector			
Cooling connectors		2 x ¾" / 19 mm			
Certifications					
Type approval		CE, EN 60034			
Environmental		Prepared for ISO 9227			
Protection grade		IP6K9K ²⁾			
Vibrations		Prepared for ISO 16750-3			
Customs tariff number		8501 5381			

1) Please contact ENGIRO for the parametrization of third-party inverters

2) Please note that the IP6K9K rating is only valid if the machine is installed with suitable cable glands and an appropriate sealed interface at the drive side of the motor (flange and/or shaft). Please contact ENGIRO for further questions. / Only applies to variants with closed B-side /


Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Available Type Variants


Flange	Shaft	Pos. sensor	B-side interface	Weight (kg)
S1 Flange with mounting threads (Ø230 mm centering, Ø250 PCD 8 x M10)	F1 Hollow shaft with screw flange (Ø90 and Ø50 mm centering, Ø66 mm PCD 10 x M10)	R Resolver	S11 Closed B-side	≈ 137 kg

Other individual combinations are also possible on request.


Technical Drawings




Front view



Rear view



Shaft end




Model	L1	L2	L3	L4	L5	L6	Moment of Inertia [kg.m²]	Cooling channel volume [L]
260W_200xx	453	45	87	115	65	155	0,1327	1,91
260W_250xx	503	95	97	115	115	65	0,1677	2,17
260W_280xx	531	125	107	120	120	75	0,1892	2,32

1) Depending on the operating points and load conditions, measures may be required to increase the coefficient of friction in the flange connection. Please contact ENGIRO for further questions.

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Simulated Efficiency of Motor Application


(electric machine only; $U_{\text{nom}} = 750 \text{ V}$)



Simulated Characteristic Motor Parameters


$U_{\text{nom}} = 750 \text{ V}$

solid lines: continuous; dashed lines: maximum;




Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.


Simulated nominal power at different coolant temperatures - $U_{nom} = 750\text{ V}$




Available torque at different coolant temperatures¹⁾



Simulated power and speed over battery voltage¹⁾



Torque over feasible maximum on time, S2 operation cycles (45°C coolant temperature)



1) solid lines: continuous; dashed lines: maximum;

Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice and are intended for general information only. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.